



STREAMLINE™

INTEGRAL DRIPPER

12060 - 12080 - 16060 - 16080 - 16100
16125 - 22080 - 22100 - 22125

TECHNICAL INFORMATION

- Recommended filtration: 130 micron / 120 mesh.
Filtration method is to be selected based on the kind and concentration of the dirt particles existing in the water. Wherever sand exceeding 2 ppm exists in the water, a Hydrocyclon filter is to be installed before the main filter. When sand / silt / clay solids exceed 100ppm, pre treatment will be applied according to Netafim™ expert team's instructions.
- TurboNet™ labyrinth with large water passage.
- To be "welded" into a thin-walled dripperlines (0.15 , 0.20 , 0.25 , and 0.31 mm).
- Injected dripper, very low CV.
- UV resistant. Resistant to standard nutrients used in agricultural.
- Streamline™ drippers meet ISO 9261 Standards with production certified by the Israel Standards Institute (SII).

DRIPPERS TECHNICAL DATA

12060, 16060 - 0.15 mm. wall thickness dripperlines

FLOW RATE*	MAX. WORKING PRESSURE** (BAR)	WATER PASSAGES DIMENSIONS WIDTH-DEPTH-LENGTH (MM.)	FILTRATION AREA (MM ²)	CONSTANT K	EXPONENT X	RECOMMENDED FILTRATION (MICRON)/(MESH)
0.80	1.4/0.8	0.58 x 0.33 x 25	14	0.265	0.48	130/120
1.10	1.4/0.8	0.51 x 0.42 x 13	15	0.392	0.45	130/120
1.60	1.4/0.8	0.66 x 0.55 x 13	17	0.568	0.45	130/120
2.20	1.4/0.8	0.66 x 0.72 x 13	17	0.780	0.45	130/120

* Flow rate at 1.0 bar pressure **According to dripperlines inside diameter

FLOW RATE (L/H.) VS. PRESSURE (BAR)

12060, 16060 – 0.15 mm. wall thickness dripperlines

FLOW RATE* (L/H.)	PRESSURE (BAR)										
	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.4
0.80	0.45	0.52	0.57	0.63	0.67	0.72	0.76	0.80	0.84	0.87	0.94
1.10	0.64	0.73	0.81	0.88	0.94	1.00	1.05	1.10	1.15	1.20	1.29
1.60	0.93	1.06	1.17	1.27	1.36	1.45	1.53	1.60	1.67	1.74	1.86
2.20	1.28	1.46	1.61	1.75	1.87	1.99	2.10	2.20	2.29	2.39	2.56

*Nominal flow rate at 1.0 bar pressure

DRIPPERS TECHNICAL DATA

12080, 16080, 22080 - 0.20 mm. wall thickness dripperlines

FLOW RATE*	MAX. WORKING PRESSURE** (BAR)	WATER PASSAGES DIMENSIONS WIDTH-DEPTH-LENGTH (MM.)	FILTRATION AREA (MM ²)	CONSTANT K	EXONENT X	RECOMMENDED FILTRATION (MICRON)/(MESH)
0.72	1.7/1.0/0.8	0.58 x 0.33 x 25	14	0.238	0.48	130/120
1.05	1.7/1.0/0.8	0.51 x 0.42 x 13	15	0.373	0.45	130/120
1.60	1.7/1.0/0.8	0.66 x 0.55 x 13	17	0.568	0.45	130/120
2.20	1.7/1.0/0.8	0.66 x 0.72 x 13	17	0.780	0.45	130/120

* Flow rate at 1.0 bar **According to dripperlines inside diameter

FLOW RATE (L/H.) VS. PRESSURE (BAR)

12080, 16080, 22080 – 0.20 mm. wall thickness dripperlines

FLOW RATE* (L/H.)	PRESSURE (BAR)										
	0.3	0.4	0.5	0.6	0.7	0.8	1.0	1.1	1.3	1.5	1.7
0.72	0.40	0.46	0.52	0.56	0.61	0.65	0.72	0.75	0.82	0.87	0.93
1.05	0.61	0.70	0.77	0.84	0.90	0.95	1.05	1.10	1.18	1.26	1.33
1.60	0.93	1.06	1.17	1.27	1.36	1.45	1.60	1.67	1.80	1.92	2.03
2.20	1.28	1.46	1.61	1.75	1.87	1.99	2.20	2.29	2.47	2.64	2.79

*Nominal flow rate at 1.0 bar pressure

DRIPPERS TECHNICAL DATA

16100, 16125, 22100, 22125 - 0.25 and 0.31 mm. wall thickness dripperlines

FLOW RATE* (L/H.)	MAX. WORKING PRESSURE** (BAR)	WATER PASSAGES DIMENSIONS WIDTH-DEPTH-LENGTH (MM.)	FILTRATION AREA (MM ²)	CONSTANT K	EXONENT X	RECOMMENDED FILTRATION (MICRON)/(MESH)
0.72	1.2/1.8/1.0/1.2	0.58 x 0.33 x 25	14	0.238	0.48	130/120
1.05	1.2/1.8/1.0/1.2	0.51 x 0.42 x 13	15	0.373	0.45	130/120
1.60	1.2/1.8/1.0/1.2	0.66 x 0.55 x 13	17	0.568	0.45	130/120
2.10	1.2/1.8/1.0/1.2	0.66 x 0.72 x 13	17	0.740	0.45	130/120

* Flow rate at 1.0 bar **According to dripperlines inside diameter and dripperlines wall thickness

FLOW RATE (L/H.) VS. PRESSURE (BAR)

16100, 16125, 22100, 22125 – 0.25 and 0.31 mm. wall thickness dripperlines

FLOW RATE* (L/H.)	PRESSURE (BAR)										
	0.3	0.4	0.5	0.6	0.7	0.8	1.0	1.2	1.4	1.6	1.8
0.72	0.40	0.46	0.52	0.56	0.61	0.65	0.72	0.78	0.84	0.90	0.95
1.05	0.61	0.70	0.77	0.84	0.90	0.95	1.05	1.14	1.22	1.30	1.37
1.60	0.93	1.06	1.17	1.27	1.36	1.45	1.60	1.74	1.86	1.98	2.09
2.10	1.21	1.38	1.53	1.66	1.78	1.89	2.10	2.26	2.43	2.58	2.72

*Nominal flow rate at 1.0 bar pressure

Dripperlines Technical Data

Model	Inside Diameter (mm.)	Wall Thickness (mm.)	Outside Diameter (mm.)	Max. Working Pressure (bar)	Maximum Flushing Pressure (bar)	KD
12060	11.8	0.15	12.10	1.40	1.6	0.15
12080	11.8	0.20	12.20	1.70	2.0	0.15
16060	16.2	0.15	16.50	0.80	0.9	0.10
16080	16.2	0.20	16.60	1.00	1.2	0.10
16100	16.2	0.25	16.70	1.20	1.4	0.10
16125	16.2	0.31	16.82	1.80	2.1	0.10
22080	22.2	0.20	22.60	0.80	0.9	0.01
22100	22.2	0.25	22.70	1.00	1.2	0.01
22125	22.2	0.31	22.82	1.20	1.4	0.01

Dripperlines Package Data (On Carton Coils)

Model	Wall Thickness (mm.)	Coil Length (m.)	Distance Between Drippers (m.)	Average* Coil Weight (kg.)	Coils per Pallet (units)	Coils in a 40 Feet Container (units)	Total in a 40 Feet Container (m.)
12060	0.15	3300	0.10 to 0.25	21.5	20	800	2640000
		3600	0.30 to 1.00	22.9			2880000
12080	0.20	2600	0.10 to 0.15	24.5	20	800	2080000
		2800	0.10 to 0.25	24.0			2240000
		3000	0.30 to 1.00	25.3			2400000
16060	0.15	2600	0.10 to 0.25	21.5	20	800	2080000
		3000	0.30 to 1.00	23.5			2400000
16080	0.20	2200	0.10 to 0.25	25.3	20	800	1760000
		2500	0.30 to 1.00	25.8			2000000
16100	0.25	1800	0.10 to 0.25	23.6	20	800	1440000
		2000	0.30 to 1.00	25.9			1600000
16125	0.31	1100	0.10 to 0.25	17.9	20	800	880000
		1300	0.30 to 1.00	20.9			1040000
22080	0.20	1600	0.10 to 0.25	23.6	16	640	1024000
		1800	0.30 to 1.00	25.6			1152000
22100	0.25	1200	0.10 to 0.25	22.0	16	640	768000
		1500	0.30 to 1.00	26.6			960000
22125	0.31	1100	0.10 to 0.25	20.8	16	640	704000
		1200	0.30 to 1.00	25.5			768000

*According to drippers spacing

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 12060 • ID 11.8 MM • KD 0.15 • FLOW RATE 0.80 L/H • INLET PRESSURE 1.2 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	57	69	78	85	90	95	98
	1%	64	82	96	108	118	127	135
	0	72	96	116	136	153	169	186
FLAT TERRAIN	-1%	79	109	136	162	187	211	234
	-2%	86	122	155	189	221	253	286
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 12060 • ID 11.8 MM • KD 0.15 • FLOW RATE 1.10 L/H • INLET PRESSURE 1.2 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	51	65	74	82	89	95	98
	1%	56	73	86	98	109	118	126
	0	61	82	100	116	131	146	158
FLAT TERRAIN	-1%	65	89	110	131	151	169	188
	-2%	70	97	123	148	172	197	221
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 12060 • ID 11.8 MM • KD 0.15 • FLOW RATE 1.60 L/H • INLET PRESSURE 1.2 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	42	54	63	70	76	82	86
	1%	45	59	70	81	89	98	105
	0	48	65	79	92	104	116	126
FLAT TERRAIN	-1%	51	69	85	101	115	130	143
	-2%	53	74	93	111	129	146	163
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 12060 • ID 11.8 MM • KD 0.15 • FLOW RATE 2.20 L/H • INLET PRESSURE 1.2 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	35	45	54	60	66	71	76
	1%	37	49	59	68	75	83	89
	0	40	53	64	75	85	95	103
FLAT TERRAIN	-1%	41	56	68	81	92	104	114
	-2%	43	59	74	88	101	114	127
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 12080 • ID 11.8 MM • KD 0.15 • FLOW RATE 0.72 L/H • INLET PRESSURE 1.2 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	59	72	81	88	93	97	100
	1%	68	86	101	114	124	134	142
	0	77	102	125	145	164	182	198
FLAT TERRAIN	-1%	86	118	147	176	203	229	255
	-2%	94	132	170	206	242	279	315
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 12080 • ID 11.8 MM • KD 0.15 • FLOW RATE 1.05 L/H • INLET PRESSURE 1.2 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	53	66	76	84	90	96	100
	1%	58	75	89	101	111	120	130
	0	63	84	103	120	136	151	165
FLAT TERRAIN	-1%	67	92	114	136	156	176	195
	-2%	72	101	128	154	179	205	230
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 12080 • ID 11.8 MM • KD 0.15 • FLOW RATE 1.60 L/H • INLET PRESSURE 1.2 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	42	54	63	70	76	82	86
	1%	45	59	70	81	89	98	105
	0	48	65	79	92	104	116	126
FLAT TERRAIN	-1%	51	69	85	101	115	130	143
	-2%	53	74	93	111	129	146	163
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 12080 • ID 11.8 MM • KD 0.15 • FLOW RATE 2.20 L/H • INLET PRESSURE 1.2 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	35	45	54	60	66	71	76
	1%	37	49	59	68	75	83	89
	0	40	53	64	75	85	95	103
FLAT TERRAIN	-1%	41	56	68	81	92	104	114
	-2%	43	59	74	88	101	114	127
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 16060 • ID 16.2 MM • KD 0.1 • FLOW RATE 0.80 L/H • INLET PRESSURE 0.8 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	65	71	74	75	76	77	78
	1%	89	107	118	127	132	137	140
	0	122	162	197	229	259	286	313
FLAT TERRAIN	-1%	153	218	281	344	407	470	231
	-2%	186	103	88	84	82	81	81
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 16060 • ID 16.2 MM • KD 0.1 • FLOW RATE 1.10 L/H • INLET PRESSURE 0.8 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	65	74	79	82	84	85	86
	1%	82	101	115	125	134	140	146
	0	103	138	168	195	220	244	266
FLAT TERRAIN	-1%	121	170	218	264	309	354	399
	-2%	142	208	276	98	92	90	88
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 16060 • IID 16.2 MM • KD 0.1 • FLOW RATE 1.60 L/H • INLET PRESSURE 0.8 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	57	66	72	77	80	81	83
	1%	68	86	98	109	118	125	130
	0	82	108	132	154	174	193	210
FLAT TERRAIN	-1%	92	128	162	196	228	260	291
	-2%	105	151	197	244	113	99	94
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 16060 • ID 16.2 MM • KD 0.1 • FLOW RATE 2.20 L/H • INLET PRESSURE 0.8 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	50	59	66	72	74	78	79
	1%	58	73	85	95	104	111	117
	0	67	89	108	126	142	158	172
FLAT TERRAIN	-1%	74	102	128	153	177	201	225
	-2%	82	116	150	184	218	252	118
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 16080 • ID 16.2 MM • KD 0.1 • FLOW RATE 0.72 L/H • INLET PRESSURE 1.0 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	76	85	89	92	94	95	95
	1%	101	122	137	148	157	163	168
	0	132	176	214	248	280	311	339
FLAT TERRAIN	-1%	162	228	292	356	418	481	544
	-2%	192	284	120	110	106	104	102
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 16080 • ID 16.2 MM • KD 0.1 • FLOW RATE 1.05 L/H • INLET PRESSURE 1.0 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	73	85	93	98	101	104	105
	1%	90	112	128	142	152	161	168
	0	108	144	176	205	231	256	279
FLAT TERRAIN	-1%	124	173	219	264	308	351	394
	-2%	142	205	268	333	128	119	114
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 16080 • ID 16.2 MM • KD 0.1 • FLOW RATE 1.60 L/H • INLET PRESSURE 1.0 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	62	74	82	89	93	97	98
	1%	72	91	106	119	129	138	146
	0	83	110	134	156	176	195	214
FLAT TERRAIN	-1%	91	126	159	190	220	250	279
	-2%	102	145	187	229	271	313	150
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 16080 • ID 16.2 MM • KD 0.1 • FLOW RATE 2.20 L/H • INLET PRESSURE 1.0 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	53	65	74	81	85	90	93
	1%	60	77	90	102	112	120	128
	0	68	90	110	128	144	160	174
FLAT TERRAIN	-1%	73	101	126	150	173	195	218
	-2%	80	113	144	175	205	236	266
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 16100/16125 • ID 16.2 MM • KD 0.1 • FLOW RATE 0.72 L/H • INLET PRESSURE 1.2 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	84	96	102	107	109	111	113
	1%	107	131	149	163	173	182	189
	0	133	177	216	251	283	314	342
FLAT TERRAIN	-1%	158	222	282	341	399	457	514
	-2%	183	268	353	448	134	129	126
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 16100/16125 • ID 16.2 MM • KD 0.1 • FLOW RATE 1.05 L/H • INLET PRESSURE 1.2 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	79	94	104	111	115	119	122
	1%	94	118	137	152	165	176	185
	0	110	146	178	207	233	259	282
FLAT TERRAIN	-1%	123	170	214	257	299	340	380
	-2%	138	197	256	315	374	173	150
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 16100/16125 • ID 16.2 MM • KD 0.1 • FLOW RATE 1.60 L/H • INLET PRESSURE 1.2 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	65	80	90	98	104	109	113
	1%	74	95	112	126	137	148	157
	0	84	112	136	158	179	199	216
FLAT TERRAIN	-1%	91	125	157	187	216	244	272
	-2%	100	141	180	219	257	296	335
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 16100/16125 • ID 16.2 MM • KD 0.1 • FLOW RATE 2.10 L/H • INLET PRESSURE 1.2 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	58	71	82	90	96	101	106
	1%	64	82	97	110	121	131	139
	0	71	94	115	134	151	167	183
FLAT TERRAIN	-1%	76	104	129	154	177	200	222
	-2%	82	115	146	177	206	236	266
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 22080 • ID 22.2 MM • KD 0.01 • FLOW RATE 0.72 L/H • INLET PRESSURE 0.8 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	75	77	78	78	79	78	78
	1%	128	140	145	149	151	153	154
	0	239	311	375	433	487	538	586
FLAT TERRAIN	-1%	367	243	180	171	166	164	162
	-2%	83	81	80	80	79	79	78
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 22080 • ID 22.2 MM • KD 0.01 • FLOW RATE 1.05 L/H • INLET PRESSURE 0.8 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	82	86	87	88	89	90	90
	1%	126	142	152	160	164	167	170
	0	196	255	308	355	399	440	481
FLAT TERRAIN	-1%	267	379	491	218	193	185	180
	-2%	98	89	86	85	85	84	84
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 22080 • ID 22.2 MM • KD 0.01 • FLOW RATE 1.60 L/H • INLET PRESSURE 0.8 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	76	82	84	87	87	88	89
	1%	107	125	138	146	152	157	161
	0	150	195	235	272	305	337	367
FLAT TERRAIN	-1%	190	266	339	412	486	561	207
	-2%	237	98	90	88	86	85	85
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 22080 • ID 22.2 MM • KD 0.01 • FLOW RATE 2.10 L/H • INLET PRESSURE 0.8 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	70	77	82	84	85	86	87
	1%	93	111	124	134	142	147	152
	0	123	160	192	222	250	275	301
FLAT TERRAIN	-1%	149	206	260	314	367	420	474
	-2%	179	259	99	92	89	88	86
DOWNTILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 22100 • ID 14.2 MM • KD 0.1 • FLOW RATE 0.72 L/H • INLET PRESSURE 1.0 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
FLAT TERRAIN	2%	91	95	96	97	97	98	98
	1%	146	164	173	180	184	186	188
	0	242	315	380	439	493	544	593
DOWNHILL	-1%	345	493	642	236	220	213	209
	-2%	111	103	101	100	100	99	99

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 22100 • ID 14.2 MM • KD 0.1 • FLOW RATE 1.05 L/H • INLET PRESSURE 1.0 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
FLAT TERRAIN	2%	96	103	106	108	109	110	110
	1%	139	162	177	187	194	200	204
	0	199	260	312	361	406	449	488
DOWNHILL	-1%	257	359	460	562	664	267	245
	-2%	323	118	111	109	107	106	106

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 22100 • ID 14.2 MM • KD 0.1 • FLOW RATE 1.60 L/H • INLET PRESSURE 1.0 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
FLAT TERRAIN	2%	87	97	102	105	107	108	109
	1%	116	139	155	167	176	183	189
	0	153	199	239	276	310	343	374
DOWNHILL	-1%	185	255	323	390	456	522	589
	-2%	222	321	124	115	112	109	108

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 22100 • ID 14.2 MM • KD 0.1 • FLOW RATE 2.10 L/H • INLET PRESSURE 1.0 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
FLAT TERRAIN	2%	81	91	97	101	103	105	107
	1%	103	124	140	153	163	171	178
	0	129	168	202	234	262	290	315
DOWNHILL	-1%	152	208	261	313	364	415	466
	-2%	178	253	329	127	118	113	111

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 22125 • ID 22.2 MM • KD 0.01 • FLOW RATE 0.72 L/H • INLET PRESSURE 1.2 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	106	111	114	115	116	116	117
	1%	160	183	197	207	212	217	221
	0	245	319	384	443	498	550	599
FLAT TERRAIN	-1%	332	468	603	739	299	274	262
	-2%	153	129	124	122	121	120	119

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 22125 • ID 22.2 MM • KD 0.01 • FLOW RATE 1.05 L/H • INLET PRESSURE 1.2 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	109	119	124	128	129	131	131
	1%	149	177	196	210	220	228	234
	0	202	263	317	366	412	454	495
FLAT TERRAIN	-1%	251	347	441	534	627	720	815
	-2%	306	167	141	135	131	130	129
DOWNHILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 22125 • ID 22.2 MM • KD 0.01 • FLOW RATE 1.60 L/H • INLET PRESSURE 1.2 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	97	109	116	121	124	127	128
	1%	123	149	168	184	196	205	213
	0	155	201	242	280	315	348	378
FLAT TERRAIN	-1%	182	249	313	376	437	498	559
	-2%	213	304	395	153	141	136	133
DOWNHILL								

MAX. LATERAL LENGTH (METERS) AT DIFFERENT SLOPES - 10% FLOW VARIATION

STREAMLINE™ • 22125 • ID 22.2 MM • KD 0.01 • FLOW RATE 2.10 L/H • INLET PRESSURE 1.2 BAR

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	88	101	110	116	119	123	125
	1%	108	132	151	166	178	188	197
	0	131	170	205	237	266	294	320
FLAT TERRAIN	-1%	150	204	254	304	352	400	446
	-2%	172	242	311	382	163	147	140
DOWNHILL								